

CA COMPLIANT ADHESIVES

IN OUR WOODWORKING ADHESIVE RANGE



L20 CA Compliant Contact Adhesive



Dry Time: 2-4 mins

Open Time: 1+ hours

Size: Aerosol 22FL OZ

22L Canister

108L Canister

216L Canister

Tensorgrip® L20 is formulated to achieve a successful, lasting bond to standard laminates and a range of other substrates while complying with strict California VOC regulations.

Advantages

- High Tack/High Strength
- Fast dry with excellent initial bond
- SCAQMD Rule 1168 Compliant

Properties

- CA Compliant
- Web Spray
- CO-REZ Technology
- Heat Resistance up to 190F*

Substrates

- Standard Laminate

Application Tool

Hose: M130
Gun: M120
Tip: UniJet® 9501B

© Quin Global US 2024

L30 Post-Formable Pebble Spray Contact Adhesive



Dry Time: 2-4 mins

Open Time: 20 mins

Size: 22L Canister

108L Canister

216L Canister

Tensorgrip® L30 is formulated specifically to eliminate telegraphing and deliver quality results for postforming applications.

Advantages

- Lower profile for thinner materials
- Excellent high coverage
- SCAQMD Rule 1168 Compliant

Properties

- Pebble Spray
- CA Compliant
- CO-REZ Technology
- HAPS free
- Heat Resistance up to 190F*

Substrates

- Standard Laminate
- Post-forming

Application Tool

Hose: M130
Gun: M120
Tip: UniJet® 4001B

www.quin-global.com

L64 Ultra-Low Profile Contact Adhesive



Dry Time: 2-4 mins

Open Time: 20 mins

Size: 22L Canister

108L Canister

216L Canister

Tensorgrip® L64 is the ONLY spray contact adhesive for bonding GLOSS decorative surfaces. It's developed to give a perfect mist spray pattern for the lowest profile available.

Advantages

- Super low profile, doesn't telegraph
- Excellent high coverage
- SCAQMD Rule 1168 Compliant

Properties

- Mist Spray
- CA Compliant
- CO-REZ Technology
- HAPS Free
- Heat Resistance up to 190F*

Substrates

- High Gloss Laminate

Application Tool

Hose: M130
Gun: M120
Tip: M201

ECR24-071-0924

L70 CA Compliant Crosslinking Contact Adhesive



Dry Time: 3-5 mins

Open Time: 20 mins

Size: 22L Canister

Tensorgrip® L70 is a revolutionary high performance, plasticizer resistant adhesive, specifically formulated for bonding vinyl, rubber and plastics. Works well on decorative surfaces subject to plasticizer migration as well as many other surfaces. Like epoxy, it chemically reacts to create permanent bonds.

Advantages

- VOC Free
- Excellent plasticizer resistance
- High output for fast application
- Semi-repositionable

Properties

- CA Compliant
- Web Spray
- Heat Resistance up to 450F*

Substrates

- Standard Laminate
- Rubber/Vinyl
- FRP/GRP
- Metal/Aluminum Sheet
- Veneers

Application Tool

Hose: M180
Gun: M120
Tip: UniJet® 9501B

*The heat resistance value is for reference only and may vary by application. Users should perform their own tests to ensure suitability.

CA Compliant Product Flyer