

# CA COMPLIANT ADHESIVES

IN OUR INDUSTRIAL ADHESIVE RANGE



## PI20 Polyurethane Bead Adhesive

Open Time: 5 mins

Size: 22L Canister



Tensorgrip® PI20 is a 100% solids, polyurethane bead adhesive with excellent temperature and chemical resistance.

### Advantages

- Ultra-fast application
- Single component; moisture cure
- Liquid-resistant
- Excellent high coverage

### Properties

- Bead Dispensing
- CA Compliant
- HAPs Free
- Low Odor
- Heat Resistance up to 350F

### Substrates

- Drywall/Plasterboard
- Plywood
- Polystyrene

### Application Tool

Hose: M130  
Gun: M160

## PI25 Polyurethane Foam Adhesive

Open Time: 5 mins

Size: 22L Canister



Tensorgrip® PI25 is a high solids, polyurethane foam bead adhesive with good temperature and chemical resistance.

### Advantages

- Ultra-fast application
- Single component; moisture cure
- Liquid-resistant
- Excellent high coverage

### Properties

- Bead Dispensing
- CA Compliant
- HAPS Free
- Heat Resistance up to 400F

### Substrates

- Polystyrene
- Plywood
- Drywall/Plasterboard

### Application Tool

Hose: M130  
Gun: M160

## P307 CA Compliant Contact Adhesive

Dry Time: 2-4 mins

Open Time: 1+ hours



Size: Aerosol 22FL OZ

22L Canister

108L Canister

216L Canister

Tensorgrip® P307 is a multi-purpose contact adhesive that effectively bonds a vast range of substrates while maintaining compliance with stringent California VOC requirements.

### Advantages

- Adheres to nearly any surface, including flexible and porous substrates
- High strength, long term bond
- SCAQMD Rule 1168 Compliant

### Properties

- Web Spray
- CA Compliant
- CO-REZ Technology
- Heat Resistance up to 175F

### Substrates

- Foam
- Insulation
- Standard Laminate

### Application Tool

Hose: M130  
Gun: M120  
Tip: UniJet® 6501B

## P308 High Tack CA Compliant Contact Adhesive

Dry Time: 2-4 mins

Open Time: 1+ hours



Size: 22L Canister

108L Canister

216L Canister

Tensorgrip® P308 is a multi-purpose contact adhesive that effectively bonds a vast range of substrates while maintaining compliance with stringent California VOC requirements (SCAQMD Rule 1168).

### Advantages

- High build is effective on porous or rough surfaces
- Aggressive high-strength, permanent bond
- High tack, flexible adhesive

### Properties

- Web Spray
- CA Compliant
- CO-REZ Technology
- Heat Resistance up to 225F

### Substrates

- Carpet
- Fabric
- FRP/GRP
- Metal/Aluminum Sheet
- Plywood

### Application Tool

Hose: M130  
Gun: M120 or M125  
Tip: UniJet® 9501B

Schedule a Demo | 402-731-3636 | sales.us@quin-global.com

# CA COMPLIANT ADHESIVES

IN OUR INDUSTRIAL ADHESIVE RANGE



© Quin Global US 2024

## P313 Low VOC Pebble Spray Contact Adhesive



**Dry Time:** 2-4 mins

**Open Time:** 20 mins

**Size:** 22L Canister

108L Canister

216L Canister

Tensorgrip® P313 is a low VOC contact adhesive; designed to deliver superior smoothness and allow post-forming while remaining within California VOC regulations.

### Advantages

- Lower profile spray reduces telegraphing
- Fast drying
- SCAQMD Rule 1168 Compliant

### Properties

- Pebble Spray
- CA Compliant
- CO-REZ Technology
- HAPs Free
- Heat Resistance up to 200F

### Substrates

- Post-Forming
- Standard Laminate
- High Gloss/Def Laminate

### Application Tool

**Hose:** M130  
**Gun:** M120  
**Tip:** UniJet® 4001B

www.quin-global.com

## P329 CA Compliant Pressure Sensitive Adhesive



**Dry Time:** 2-4 mins

**Open Time:** 1+ hours

**Size:** Aerosol 22FL OZ

22L Canister

108L Canister

216L Canister

Tensorgrip® P329 is a very aggressive, high build pressure sensitive adhesive designed to bond porous substrates while maintaining a high level of tack. Useful for bonding for Foam, Insulation, Metals and Wood.

### Advantages

- Very aggressive, high tack adhesive
- High build web spray
- High strength, long term bond
- 100% Adhesive transfer to substrate
- SCAQMD Rule 1168 Compliant

### Properties

- Web Spray
- CA Compliant
- CO-REZ Technology
- HAPs Free
- Heat resistance up to 150F

### Substrates

- Metal/Aluminum Sheeting
- Foam
- Fabric
- Plywood
- Corner Bead

### Application Tool

**Hose:** M130  
**Gun:** M120  
**Tip:** UniJet® 110015B

ECR24-071-0924

## P607 Fire Rated CA Compliant Contact Adhesive



**Dry Time:** 2-4 mins

**Open Time:** 1+hours

**Size:** Aerosol 22 FL OZ

22L Canister

108L Canister

216L Canister

Tensorgrip® P607 is a Class A Fire Rated multi-purpose contact adhesive that effectively bonds a vast range of substrates while maintaining compliance with stringent California VOC requirements. Fire rated testing includes ASTM E1354 test method for heat and visible smoke release complying with FMVSS 302 Standards.

### Advantages

- Class A Fire Rated
- High strength, long term bond
- SCAQMD Rule 1168 Compliant
- 100% adhesive transfer to substrate

### Properties

- Web Spray
- CA Compliant
- CO-REZ Technology
- Heat Resistance up to 175F

### Substrates

- Foam
- Plywood
- FRP/GRP
- Metal/Aluminum Sheeting

### Application Tool

**Hose:** M130  
**Gun:** M120  
**Tip:** UniJet® 6501B

CA Compliant Product Flyer

## P809 CA Compliant Crosslinking Contact Adhesive



**Dry Time:** 3-5 mins

**Open Time:** 20 mins

**Handling Strength:** 1-2 hours

**Size:** 22L Canister

**Full Cure Time:** 1-3 days

Tensorgrip® P809 is a revolutionary high performance, plasticizer resistant adhesive, specifically formulated for bonding vinyl, rubber and plastics. Works well on decorative surfaces subject to plasticizer migration as well as many other surfaces. Like epoxy, it chemically reacts to create permanent bonds.

### Advantages

- Bonds vinyl permanently
- VOC Free
- Excellent plasticizer resistance
- High output for fast application
- Semi-repositionable

### Properties

- Web Spray
- CA Compliant
- Heat Resistance up to 450F

### Substrates

- Vinyl
- Standard Laminate
- FRP/GRP
- Metal/Aluminum Sheeting

### Application Tool

**Hose:** M180  
**Gun:** M120  
**Tip:** UniJet® 11001B