

Tensorgrip®



S103

CA COMPLIANT ADHESIVE REMOVER

Tensorgrip® S103 Aerosol is a California-compliant, general-purpose adhesive remover, designed for safe and efficient cleanup of adhesive overspray, decal residue, and equipment surfaces. Suitable for use on a wide range of non-porous substrates, S103 aerosols delivers reliable performance with a fast-acting, low-odor formula. S103 in canisters is excellent for gun and hose clean outs. Features CO-REZ Technology, which is an exceptional formulation incorporating a highly engineered resin and gas matrix. The result: Greater Coverage from Less Weight.

ADVANTAGES

- Versatile, general-purpose use: safe to use on most plastics and non-porous substrates
- CARB & SCAQMD 1171 Compliant: low VOC formulation supports a safer, healthier workspace
- Quick-acting and effective formula: dissolves adhesives in 1-3 minutes
- Pleasant fragrance
- High transfer efficiency, reducing waste

TECHDATA

OPEN TIME



3 Minutes

COLOR



Clear

SUITABLE FOR



Standard Laminate



Metal / Aluminum
Sheeting



Plastics



Concrete

PROPERTIES



Mist Spray



CA Compliant



CO-REZ™
Technology

TYPICAL PROPERTIES	
VOC Content	15% by weight (Aerosol), 11 g/L (Canister)
Color	Clear
System Flammability	Flammable
Solvent System	Acetone Blend
Dry time	1-3 minutes depending on temperature and humidity
Open time	3 minutes dependent on temperature and humidity
Shelf Life	18 months from date of manufacture
PACKAGING	
650 ml	Aerosol Can
7L	Disposable Canister
22L	Disposable Canister
REGULATORY	
SCAQMD Rule 1168 Compliant	Yes (Canisters)
CARB Compliant	Yes (Aerosols)

DIRECTIONS FOR USE

For Surface Cleaning:

1. Test for compatibility in inconspicuous area before use.
2. Hold applicator 6"-10" from surface.
3. Apply even, generous coat of cleaner on the surface.
4. Wait 1-3 minutes before wiping for best cleaning performance.

For Spray Gun and Hose Clean-out (Canisters only):

1. Disconnect spray gun and hose from adhesive canister.
2. Immediately connect to cleaner canister, and open canister valve.
3. Flush out spray gun and hose for until clear (approx 45 seconds).
4. Close canister valve and bleed pressure before disconnecting hose.

Canister or aerosol will spray adequately above 60°F and should be kept in a warm area. In the event that the container gets abnormally chilled, freezes or gives poor or sputtering spray, it should be warmed up before continued usage. Warming canister by immersion in warm water is recommended.

HANDLING & STORAGE

- Consult Safety Data Sheet prior to use.
- Store between 60°F (15°C) and 120°F (50°C).
- Do not store directly on concrete floor.
- Avoid exposure to direct sunlight.
- Always test product to determine suitability for your particular application prior to use in production.

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 11/7/2025 Version: 1.0 ECR25-049

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Tensorgrip S103 CA Compliant Adhesive Remover Canister
Product code : S103-7, S103-22

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive Canister Equipment Solvent Flush
Restrictions on use : For industrial/occupational use only

1.4. Supplier's details

QUIN GLOBAL US, Inc
5510 F Street
OMAHA, NE 68117 United States
T 402 731 3636
marketing.us@quin-global.com - www.quentinglobal.com

1.5. Emergency phone number

Emergency number : CHEMWATCH EMERGENCY RESPONSE (24/7) +1 855- 237-5573 +61 3 9573 3188

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Chemical under pressure, Category 1	H282	Extremely flammable chemical under pressure: May explode if heated.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H282 - Extremely flammable chemical under pressure: May explode if heated
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P261 - Avoid breathing vapors.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective gloves.
P302+P352 - If on skin: Wash with plenty of soap and water.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical attention.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P370+P378 - In case of fire: Use ABC-powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish.
P381 - In case of leakage, eliminate all ignition sources.
P376 - Stop leak if safe to do so.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents and/or container to an approved waste disposal plant.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Acetone	CAS-No.: 67-64-1	80-100
CO-REZ Propellant	CAS-No.: QG0001**	5-10
D-Limonene	CAS-No.: 5989-27-5	1 – 5

Comments

: *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
** Unique identifier is a company internal designation.

Full text of hazard classes and H-statements : see section 16

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.
Skin	: May cause slight irritation to the skin. May cause an allergic skin reaction.
Eyes	: Causes serious eye irritation. redness, itching, tears.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: None known.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: If necessary seek medical advice. Treat symptomatically.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use dry chemical, CO2, water spray or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable chemical under pressure: May explode if heated. vapors may cause fire/explosion if source of ignition is present. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Explosion hazard	: vapors may form explosive mixture with air.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO2). Organic compounds.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Use self-contained breathing apparatus and chemically protective clothing. Use shielding to protect from bursting cans.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate all ignition sources. No open flames, no sparks, and no smoking. Ventilate spillage area.
------------------	---

For non-emergency personnel

Emergency procedures	: Avoid breathing vapors. Avoid contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : If safe, move leaking containers outdoors or to a well-ventilated area. Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from heat and direct sunlight. Do not puncture or incinerate containers.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep cool. Protect from sunlight.

Incompatible materials : Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

CO-REZ Propellant (QG0001**)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	9000 mg/m ³
	5000 ppm
ACGIH® TLV® STEL	54000 mg/m ³
	30000 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA)	9000 mg/m ³
	5000 ppm
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Acetone (67-64-1)	
ACGIH® TLV® TWA	594 mg/m ³ 250 ppm
ACGIH® TLV® STEL	1187 mg/m ³ 500 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	Acetone
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL (TWA)	2400 mg/m ³ 1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

Chemically resistant protective gloves. Consult supplier for specific recommendations.

Eye protection:

Chemical goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Color : Colorless

Odor : Solvent

Odor threshold : No data available

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 54 °C
Flash point	: -21 °C (-5.8°F)
Flammability (solid, gas)	: Extremely flammable chemical under pressure: May explode if heated.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: 0.7 – 6.1 vol %
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 11 g/l
-------------	----------

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Protect from sunlight.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

D-Limonene (5989-27-5)

LD50 oral rat	> 2000 mg/kg body weight
---------------	--------------------------

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

D-Limonene (5989-27-5)	
LD50 dermal rabbit	> 5000 mg/kg
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg body weight Animal: rat, Animal sex: female
LD50 oral	6667 mg/kg
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Acetone (67-64-1)	
NOAEL (oral, rat, 90 days)	900 mg/kg bw/day
Aspiration hazard	: Not classified
Symptoms/effects	: May cause drowsiness or dizziness.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes. High concentration of vapors may induce: headache, nausea, dizziness.
Skin	: May cause slight irritation to the skin. May cause an allergic skin reaction.
Eyes	: Causes serious eye irritation. redness, itching, tears.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: None known.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Hazardous to the aquatic environment, short-term : Harmful to aquatic life.

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

D-Limonene (5989-27-5)

LC50 - Fish [1]	720 µg/l Pimephales promelas (Fathead minnow)
EC50 - Crustacea [1]	0.36 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	≈ 8 mg/l Desmodesmus subspicatus
NOEC (chronic)	0.115 mg/l Daphnia magna (Water flea)
NOEC chronic fish	0.08 mg/l

Acetone (67-64-1)

LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
EC50 - Crustacea [1]	12600 – 12700 mg/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Quin 1487 CA Compliant Solvent Flush Canister

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

CO-REZ Propellant (QG0001**)

Persistence and degradability	Biodegradation is not applicable to inorganic compounds.
-------------------------------	--

D-Limonene (5989-27-5)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Acetone (67-64-1)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

Acetone (67-64-1)

Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0.23

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Do not puncture or incinerate, even when empty.

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3501	UN3501	3501	3501
14.2. Proper Shipping Name			
Chemical under pressure, flammable, n.o.s. (Acetone)	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Acetone)	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Acetone)	Chemical under pressure, flammable, n.o.s. (Acetone)
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN3501

TDG

UN-No. (TDG) : UN3501

Emergency Response Guide (ERG) Number : 115

IMDG

Special provision (IMDG) : 274, 362

Limited quantities (IMDG) : 0

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P206

Packing provisions (IMDG) : PP89

Tank instructions (IMDG) : T50

Tank special provisions (IMDG) : TP4, TP40

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D

Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : Liquids, pastes or powders, pressurized with a propellant which meets the definition of a gas.

IATA

Special provision (IATA) : A1, A187

PCA Excepted quantities (IATA) : E0

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: Forbidden
PCA max net quantity (IATA)	: Forbidden
CAO packing instructions (IATA)	: 218
CAO max net quantity (IATA)	: 75kg
ERG code (IATA)	: 10L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

CO-REZ Propellant (QG0001**)

Listed on the Canadian DSL (Domestic Substances List)

D-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Acetone (67-64-1)

Listed on ELINCS (European List of Notified Chemical Substances)

National regulations

D-Limonene (5989-27-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Acetone (67-64-1)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Tensorgrip S103 CA Compliant Adhesive Remover Canister

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Issue date : 11/7/2025

Full text of hazard classes and H-statements

H282	Extremely flammable chemical under pressure: May explode if heated
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.